



Electrodes / Pouch Electrodes / Case

APPLICATION

For: Hours

MR Co

PRODUCT INFORMATION

Shape Size (excl. grip) Sensor (Eyelet) Diameter Substrate Thickness (adapter excluded) Total Product Surface Area Gel Area Adhesive Area Integrated Lead Wire (length / color)

MATERIALS

Substrate Material Adhesive Gel Type Foam (Sponge) Material Release Liner Sensor Polymer Adaptor / Connector (Stud) Integrated Lead Wire Jacketing Integrated Lead Wire Cord

ELECTRICAL PERFORMANCE (ANSI/AAMI EC 12)

| ACZ impedance (before defib simulation) @10 Hz | Ohm |
|---|--------|
| DC Offset Voltage (before defib simulation) | mV |
| SDR Slope (remaining potential after defib) @ 30 Sec int. | mV/sec |
| ACZ impedance repeat (after defib simulation) | Ohm |
| COIIN (combined offset instability and inner noise) | μV |
| Bias Current Tolerance (DC offset voltage after DC loading) | mV |

FEATURES MR Conditional X-ray Translucence Integrated Abrader Repositionability

Solid Gel

PACKAGING

| Product Packaging Material | |
|--------------------------------------|----|
| Resealable Pouch | |
| Product Packaging Size (L x W) | in |
| | cm |
| Department Packaging - Box (L x W) | in |
| | cm |
| Transport Packaging - Carton (L x W) | in |
| | cm |

BIOCOMPATIBILITY

ISO 10993 Latex Free

ENVIRONMENTAL

Halogenated Hydrocarbon Content (e.g. PVC) Phthalate Derivatives Content (e.g. DEHP) RoHS Compliant REACH Compliant

SHELF LIFE

Product Shelf Life (in accordance with storage guidelines)

REGULATORY STATUS

Reorder Part Number:

© 2024 Nissha Medical Technologies. All Rights Reserved. Disclaimer: The information presented is believed to be reliable concerning the subject matter covered. The final determination of the accuracy or completeness of any information, and the suitability of

the product for the use contemplated, is the responsibility of the user.